




sectional drawing A-A



**TECHNICAL CHARACTERISTICS**

MATERIAL

>Basic: PC UL HB

MOUNTING INSTRUCTION

>For reflow soldering only to be fitted after the soldering process

PACKAGING INFORMATION

>Tray

Scale - 2:1

P/N	Laser carving sign	Base color
714 409 000	No	transparent

This electronic component is designed and developed with the intention for use in general electronics equipments.

Before incorporating the components into any equipments in the field such as aerospace, aviation, nuclear control, submarine, transportation, (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc. where higher safety and reliability are especially required or if there is possibility of direct damage or injury to human body, Würth Elektronik must be asked for a written approval.

In addition, even electronic component in general electronic equipments, when used in electrical circuits that require high safety, reliability functions or performance, the sufficient reliability evaluation-check for the safety must be performed before by the user before usage.

Projection				GENERAL TOLERANCE .x = +/- 0,2 .xx = +/- 0,15		Basic material					
				Date	Name	DESCRIPTION					
				Drawn	12-10-15	Jelisarow	SwCaps				
				Checked			Caps 12x12mm illuminated tact switch WS-TLT				
						Scale	2:1	Position		SIZE	
						Drawing.- No. 714409000					A4
REV	FILE	DATE	BY	EDV NO 714409000.dft		System: Solid Edge ST7					